


TENAX

C-Flex

Bi-oriented Net



AVAILABLE ROLL DIMENSIONS AND WEIGHT

ENGLISH		METRIC	
Dimensions	Weight	Dimensions	Weight
4.0' x 330.0'	25.4 lb	1.20m x 100.0m	11.5 kg
5.0' x 330.0'	31.5 lb	1.50m x 100.0m	14.3 kg
6.0' x 100.0'	16.1 lb	1.80m x 30.5m	7.3 kg
6.0' x 330.0'	38.3 lb	1.80m x 100.0m	17.4 kg
7.5' x 100.0'	19.8 lb	2.30m x 30.5m	9.0 kg
7.5' x 330.0'	48.9 lb	2.30m x 100.0m	22.2 kg

PHYSICAL CHARACTERISTICS

	NOTES
POLYMER TYPE	Polypropylene
STRUCTURE	Quadrangular
COLOR	Black
PACKAGING	Rolls in Clear Bags with Label

DIMENSIONAL CHARACTERISTICS

	ENGLISH		METRIC		NOTES
	UNIT		UNIT		
MD PITCH	in	1.77	mm	45	a, c
TD PITCH	in	1.97	mm	50	b, c

TECHNICAL CHARACTERISTICS

	ENGLISH		METRIC		NOTES
	UNIT		UNIT		
MD TENSILE STRENGTH	lbs / ft	377	kN/m	5.5	a, c
MD ELONGATION	%	15	%	15.0	a, c
TD TENSILE STRENGTH	lbs / ft	685	kN/m	10.0	b, c
TD ELONGATION	%	10	%	10.0	b, c

NOTES:

- a Longitudinal direction
- b Transversal direction
- c All dimensions and properties are reported as typical values.

TENAX[®]

4800 East Monument Street
Baltimore, MD 21205
(P) 1-800-356-8495
(F) 1-877-836-2987
www.tenaxus.com